INSPECTION CHECKLIST

Common Fire & Life Safety Deficiencies

Y = Meets Requirements; N= Does Not Meet Requirements

Υ	Ν		ΥΙ	N		
EXTERIOR:			UTILITY/MECHANICAL/HVAC:			
		Fire Lanes marked/unobstructed (IFC 503.3, 503.4) Address visible (IFC 505.1) Fire hydrants/water supply accessible (IFC 508)			Shut off valves present on gas appliances (IFC 603.1) Approved piping, connections & appliances used (IFC 603.1.2)	
		Combustible accumulations/storage acceptable (IFC 304.2, IFC 315.3) F.D. key box present/maintained (IFC 506)			Combustion air supply/venting present (IFC 603.1) Adequate clearance between combustibles and appliances (IFC 305.1, 603.5.3)	
0		F.D. connections visible/maintained (IFC 912) Gas meter/piping protected against impact (IFC 312, 603.9)			Commercial hood ducts/filters are clean (IFC 904.11.6.3)	
•				SPRINKLER SYSTEM:		
		EATURES/MEANS OF EGRESS: Adequate number of exits (IFC 1004.4, 1015, 1019, 1027.23)			Coverage is adequate (IFC 903.3.1) Controls are readily accessible (IFC 903.3.1) Valves locked open (IFC 903.4.4)	
		Exits, aisles, & corridors free of obstructions (IFC 1028.3)			System and valves supervised [>20 sprinklers new, ≥ 100 in existing] (IFC 903.4)	
		Exit doors open from inside (IFC 1008.1.8) Exit signs present (IFC 1011, 1027.3)			Heads in good condition (IFC 903.3.1) Wrench/spare sprinklers present (IFC 903.3.1)	
		Emergency lighting present & operational (IFC 1006, 1027.5)			Tested/inspected at least annually (IFC 903.6.1) Riser/pump rooms labeled (IFC 510.1)	
		Interior finish acceptable (IFC 803, 804) Exit corridors rated (IFC 1017.1, 1027.17.1)	EIDI	= ^	LARM & DETECTION SYSTEMS:	
					Control panel/annunciator panel in normal condition	
	DNS.	TRUCTION FEATURES: Fire rated construction present/maintained			[no trouble or alarm conditions] (IFC 901.6, 901.7) Detectors properly installed (IFC 907)	
_		(IFC 703.1) Incidental use areas separated/sprinklered			Tested/inspected at least annually (IFC 907.20)	
		(IFC 705.3) Rated fire doors operational (IFC 703.2)			R FIRE PROTECTION SYSTEMS:	
	<u> </u>	Vertical openings protected (IFC 704.2)			Standpipes needed (IFC 905) Standpipes/hose in good condition (IFC 905.2)	
STORAGE:					Adequate coverage (IFC 905.2) Hood system fuel shutoff present (IFC 904.11.2)	
		Storage neat and orderly (IFC 315.2)			Hood system properly maintained/serviced	
		Combustible storage prohibited in electrical equipment rooms, restrictions apply in boiler/mechanical rooms			(IFC 904.11.6)	
		(IFC 315.2.3)			RICAL:	
		Attic storage (IFC 315.2.4) Storage maintained [2' below ceiling un-sprinklered,			No electrical hazards (IFC 605.1, 605.6) Appliances/fixtures in good condition (IFC 605.7)	
		18" sprinklered] (IFC 315.2.1) Rubbish/waste subject to spontaneous ignition shall be			Overcurrent protection present (IFC 605.1) Power taps not used (IFC 605.4)	
		disposed of daily and in listed container		ū	Extension cords not substituted for fixed wiring	
		(IFC 304.3.1) Decorations (foams, curtains, drapes, hangings) to be			(IFC 605.5) Power strips properly used (IFC 605.4)	
		flame resistant in assembly occupancies (IFC 807.1, 807.4.2)			Access/clearance to electrical panels (IFC 605.3)	
FLAMMABLE/COMBUSTIBLE LIQUIDS:					RDOUS MATERIALS:	
		Safety containers if used (IFC 3405.2.4)			Compressed gas cylinders secured (IFC 3003.5) Rooms/areas properly labeled (IFC 2703.5)	
		Not stored/kept near exits (IFC 3404.3.3.3)			Acceptable quantities (IFC 2703.1.1)	
		No sources of ignition (IFC 3404.2.4) Quantities >10 gals in cabinet (IFC 3404.3.4.4)			Separation of incompatible materials (IFC 2703.9.8)	

This checklist is intended as a guide to assist fire inspection personnel in identifying general fire and life safety hazards, other possible code requirements may apply. Please refer to other checklists for information on certain occupancies/topics.

Adequate ventilation (IFC 3405.3.7.5.1)